

DeTERIC LP

DeTERIC LP, sodium lauriminodipropionate, CAS# 14960-06-6, is a versatile, high foaming amphoteric surfactant which finds use in a wide variety of HI&I cleaning formulations. Due to its mildness, it's also well suited for Personal Care applications. **DeTERIC LP** is readily biodegradable and exhibits low toxicity. INCI Name: Sodium Lauriminodipropionate

SPECIFICATIONS

Appearance @ 25°C:	Light yellow liquid
% Solids:	29.0 – 31.0
pH (as-is):	7.0 +/- 1.0
Color (Gardner):	3.0 max.

SOLUBILITY DeTERIC LP is soluble in water, glycols and alcohols; insoluble in oils and solvents.

TYPICAL PROPERTIES

Density @ 25°C	~1.0 g/ml
Zwitterion pH Range	~2.4 – 4.2

- Excellent hydrotrope & solubilizing properties
- Wetting, emulsification, & detergency
- High foaming properties
- Excellent stability in strong alkali, acid, & high concentrations of electrolytes
- Solutions in the isoelectric range (pH ~2.4 - 4.2) may not be clear, but will maintain high foaming properties & fast wetting
- Compatible with anionic, cationic & nonionic surfactants
- Brine Stability
- Hard water stability
- Approved for use as inert in non-food pesticide formulations
- Approved for food use as inert under 40CFR180.910, 920, & 930
- Low skin & eye irritation
- Low toxicity & readily biodegradable
- Exhibits **corrosion protection** in hard water and strong acids

APPLICATIONS

- High foaming food plant cleaners
- High caustic & alkaline cleaners
- High alkaline oven cleaners
- Strong acid cleaners
- Emulsifier for vinyl acetate/ethyl acrylate & vinyl chloride systems
- All purpose, hard surface cleaners
- Aerosol cleaners
- Foaming agent in oil drilling
- Fire fighting foam
- High foam car & truck wash
- Hand dishwashing detergents
- Mild personal care cleansers
- Solubilizer for quaternary & halogenated germicides

Continued


Amtec Center • 6421 Congress Avenue • Boca Raton, FL 33487 • (561) 994-9696 • FAX (561) 994-9995
www.DeForestEnterprises.com • info@DeForestent.com

The information and suggestions given are drawn from data we believe to be reliable, but in all cases the user should check and confirm the suggestions and results in his/her own use before proceeding further. DeFOREST Enterprises, Inc. offers no warranties other than to guarantee the products are manufactured to specifications and cannot assume any liability or risk involved in the use of our products since these conditions of use are beyond our control. None of the suggestions or recommendations constitute freedom from any patents that may be existent in the field or be issued.

Hydrotrope Properties of DeTERIC LP

DeTERIC LP is the superior hydrotrope when compared to other high foaming amphoteric surfactants in several electrolytic systems. To determine hydrotrope capabilities, a series of cloud point tests were performed with 3% NPE-9 and 2.5% hydrotrope in the electrolytes listed below.

The higher the cloud point temperature, the more efficient the hydrotrope.



Continued

Corrosion Inhibition Properties of DeTERIC LP


ACID CORROSION PROTECTION: Metal panels were submerged in the **acid solutions** and placed in sealed jars at room temperature and observed for signs of corrosion.

Cold-Rolled Steel

5% active Hydrochloric Acid, 72 hours

Control, no inhibitor


DeTERIC LP, 1% by wt.



5% active Sulfuric Acid, 72 hours

Control, no inhibitor

DeTERIC LP, 1% by wt.




HARD WATER CORROSION PROTECTION: Metal panels were submerged in **hard water** (100 ppm as CaCO₃ and 71 ppm as chloride) in sealed jars at room temperature and observed for signs of corrosion over time. The following photos were taken at 72 hours.

Cold-Rolled Steel, 72 hours

Control, no inhibitor


DeTERIC LP, 0.5% by wt.



Aluminum, 72 hours

Control, no inhibitor

DeTERIC LP, 0.5% by wt.



Metal Panels:

Steel Panels: Q-Panel – Type RS – low carbon, cold-rolled steel, 0.063” thick, ½ hard
 Aluminum Panels: Q-Panel – Type AR - Alloy 2024T3 bare, 0.063” thick, 120 hardness

Amtec Center • 6421 Congress Avenue • Boca Raton, FL 33487 • (561) 994-9696 • FAX (561) 994-9995
www.DeForestEnterprises.com • info@DeForestent.com

The information and suggestions given are drawn from data we believe to be reliable, but in all cases the user should check and confirm the suggestions and results in his/her own use before proceeding further. DeFOREST Enterprises, Inc. offers no warranties other than to guarantee the products are manufactured to specifications and cannot assume any liability or risk involved in the use of our products since these conditions of use are beyond our control. None of the suggestions or recommendations constitute freedom from any patents that may be existent in the field or be issued.